



AZ-M69

Arizon RFID Technology, 100% owned by YFY Group, is a leading company to provide first-class manufacturing services of inlays / tags / tickets and cards for worldwide RFID industry. By 2012 Arizon has produced and delivered more than 1 billion inlays / tags and the number is 10 billion pcs by Apr. of 2019, all products conform to highest quality standards in HF and UHF technology for its valuable customers. Arizon has established inlay/label monthly capacity up to 300 million pieces by 2018, and will continue its strong investments to further boost its monthly production capacity for satisfying the market's fast growing needs.

Overview

Operating Frequency

860MHz-960MHz

Integrated Circuit(IC)

Impinj Monza R6

Antenna Size

35x18mm

1.37x0.7inch

Protocol

EPC Class1 Gen2

ISO/IEC 18000-6C

Application Areas

Brand Protection

Industry/Retail/Microwave Tag

Supply Chain Management

Electrical Characteristics

Antenna

AZ-M69

Base Material

PET

IC

Impinj Monza

R6

R6-A

R6-P

S6-C

Memory

EPC:	96Bits	96Bits	128(96)Bits	96Bits
User:	0Bits	0Bits	32(64)Bits	32Bits
TID:	48Bits	48Bits	48Bits	48Bits
Unique TID:	48Bits	48Bits	48Bits	48Bits
Access Password:	0Bits	32Bits	32Bits	32Bits
Kill Password:	0Bits	32Bits	32Bits	32Bits

IC Life

100,000 Programming cycles

50 years data retention

Operating Mode

Passive

Frequency

860 ~ 960MHz

Standards

ISO 9001:2008

ISO 14001:2004


OHSAS 18001:2007





Arizon RFID Technology Co., Ltd.

Frequency Sweep





Test power : 4W EIRP

For countries that allow 2W ERP, please reduce the result by 11%

Radiation Patterns

Angular Sensitivity (dBm) ; Power step 0.1dB ; Angle step 10°




Usage Method




Bento Fully attached



Bento Half attached



Rice Balls Fully attached



Rice Balls Half attached

Arizon RFID Testing Center:

RFID UHF Band: 800-1000MHz; Shielding effectiveness: > 100 dB; Background noise: < -75 dB

Compatible to the following international standard:

EPC Global Class1 Gen2; ISO 18000-6C; GS1 TIPP (Tagged Item Performance Protocol)