



永道射频技术股份有限公司
Arizon RFID Technology Co., Ltd.



AZ-H83

Arizon RFID Technology, 100% owned by YFY Group, is a leading company to provide first-class manufacturing services of inlays / tags / tickets and cards for worldwide RFID industry. By 2012 Arizon has produced and delivered more than 1 billion inlays / tags and the number is 10 billion pcs by Apr. of 2019, all products conform to highest quality standards in HF and UHF technology for its valuable customers.

Arizon has established inlay/label monthly capacity up to 300 million pieces by 2018, and will continue its strong investments to further boost its monthly production capacity for satisfying the market's fast growing needs.

Overview

Operating Frequency

860MHz-960MHz

Integrated Circuit(IC)

NXP UCODE8

Antenna Size

70X14mm

2.756X0.551inch

Protocol

EPC Class1 Gen2

ISO/IEC 18000-6C

Application Areas

Brand Protection

Industry/Retail

Supply Chain Management

Electrical Characteristics

Antenna

AZ-H83

Base Material

Paper

IC

NXP

UCODE8

UCODE8m

Memory

EPC:

128Bits

96Bits

User:

0Bits

32Bits

TID:

48Bits

48Bits

Unique TID:

48Bits

48Bits

Access Password:

32Bits

32Bits

Kill Password:

32Bits

32Bits

IC Life

100,000 Programming cycles

50 years data retention

Operating Mode

Passive

Frequency

860 ~ 960MHz

Standards

ISO 9001:2008

ISO 14001:2004

OHSAS 18001:2007

Web site: www.arizonrfid.com

Copyright © 2019 Arizon RFID Technology Corporation



All rights reserved





Arizon RFID Technology Co., Ltd.

Frequency Sweep




Test power : 4W EIRP


For countries that allow 2 W ERP, please reduce the result by 11%

Radiation Patterns

Angular Sensitivity (dBm) ; Power step 0.1dB ; Angle step 10°



Angular Sensitivity
(Relative Read Range vs. Orientation)



Angular Sensitivity
Inlay is rotated in the x,y axis, fixed in z axis
(Tag shown at 0° with respect to face of antenna)

Arizon RFID Testing Center:

RFID UHF Band: 800-1000MHz; Shielding effectiveness: > 100 dB; Background noise: < -75 dB

Compatible to the following international standard:

EPC Global Class1 Gen2; ISO 18000-6C; GS1 TIPP (Tagged Item Performance Protocol)